

LED wall mounted exit signs

General purpose maintained or non maintained emergency escape signage with a choice of ISO 7010 or EURO legends. SmartScan, DALI / Self-Test and Standard Emergency. Available in three hour emergency versions. Applications: offices, retail, schools

- Extremely long LED lifetime, up to 100,000 hours
- 34 m maximum viewing distance in accordance with BS EN 1838
- Three hour, maintained or non-maintained emergency operation
- Choice of legends
- Simple to install, full status reporting SmartScan wireless communication versions

Notes: Two batteries required per luminaire



IP40

0 LL/CW

Specification

Mounting	Surface	IP rating	IP40
----------	---------	-----------	------

Emergency data

Legend type	EURO arrow down EURO arrow left EURO arrow right ISO 7010 arrow down ISO 7010 arrow left ISO 7010 arrow right ISO 7010 arrow up	Maximum viewing distance	34 m
Emergency type	Maintained Non-maintained	Emergency duration	3 hours
Battery specification	Nickel Metal Hydride (NiMH)		

Power

LED power	4 W	Circuit power	6 W
-----------	-----	---------------	-----


LED characteristics

Colour temperature	4000 K		
--------------------	--------	--	--

Compliance

UKCA	Yes	CE	Yes
------	-----	----	-----

Dimensions





Click or scan here
View Exit Sign variants using
our online filtering tool



Information is correct as of 01 Jan 2025, however must not be interpreted as a guarantee of individual product performance and/or characteristics. We reserve the right to alter specifications and designs without prior notice.